

MACH = RECON

30 KW

PEAK POWER
(Electrical Power)

155 KM/H

MAX SPEED (Company Tested)

100 NM

PEAK MOTOR TORQUE 231 KM

CITY RANGE (WMTC)



DESIGN

LASER



Turbo Red



Afterburner Yellow

SHADOW



Stealth Grey



Asteroid Grey

F SERIES -JET INSPIRED

DESIGN SERIES

DYNAMIC, RACE-BRED

STANCE

PARALLAX & RADAR

CONSOLE THEMES



PERFORMANCE

POWER 30 KW 20 KW

PEAK POWERNET POWER(Electrical Power)(ECE R85)

9.5 KW @ 3000 RPM

CONTINUOUS POWER (ECE R85)

TORQUE 100 NM

PEAK MOTOR TORQUE

SPEED 155 KM/H 139 KM/H

MAX. SPEED TOP SPEED (Company tested) (ECE R39.01)

ACCELERATION 2.8 SEC 7.7 SEC

0-60 KM/H 0-100 KM/H

REGENERATIVE 10 LEVELS DYNAMIC

BRAKING REGEN

RIDE MODES GLIDE, COMBAT, BALLISTIC

REQUIRED A1 LICENSE

RANGE 231 KM 143 KM

CITY RANGE
(As per WMTC)

HIGHWAY RANGE
(As per WMTC)



SMART TECH

VIOLETTE A.I.

DELTA WATCH Optional

LOCKDOWN Optional

ANTI-COLLISION WARNING SYSTEM Optional

CRASH ALERT Optional

DAILY RIDE ANALYTICS Optional

CONTROL CENTER Multi-function 5" TFT display with tactile

input switch console (L+R)

OPERATING SYSTEM UV Automotive Linux OS

SAFETY Auto dimming LED Headlight with Ultra-V

position lamp

Dual LED tail light assembly with central

brake light

Front and Rear LED Hazard Lights

Sidestand Sensor

TRACTION CONTROL 4 levels

HILL HOLD Included

ABS Mono & Dual Channel

D.S.C - DYNAMIC STABILITY Included

CONTROL





CHARGE LIMIT Included

PARK ASSIST Included

FIND MY F77 Included

DEEP SLEEP Included

TPMS Included

BATTERY SYSTEM

BATTERY PACK SRB₁₀

ENERGY CAPACITY 10.3 kWh

ENCLOSURE All-Aluminum IP67-rated enclosure

BMS & SAFETY PROTOCOLS Battery Management System with patented

5-level safety system - Mechanical, Thermal,

Electrical, Electronic & Software protection

BATTERY & DRIVETAIN WARRANTY

UV CARE 5 years or 100.000 km included

VEHICLE WARRANTY

STANDARD WARRANTY (VEHICLE)

3 years or 30.000 km included



CHARGING

CHARGING PORT IEC 62196-6

BOOST CHARGER Included

CHARGE RATE 20% - 80% in 2.5 hrs

DRIVETRAIN

MOTOR Permanent Magnet AC Motor

THROTTLE CONTROL Ride-by-wire

MECHANICAL

FRAME Steel Trellis with Aluminium Bulk Head

FRONT SUSPENSION Upside-down Telescopic fork with a diameter

of 41 mm. Preload adjustable

REAR SUSPENSION Monoshock - preload adjustable

BRAKE SYSTEM Hydraulic disc brakes with dual-channel

BOSCH ABS

BRAKE CALIPERS Front: Fixed 4-Radial Piston Type

Rear: Single Piston Floating Caliper Type

BRAKE ROTOR Front: 320mm disc Rear: 230mm disc

TYRES Front: 110/70 R17 Rear: 150/60 R17





CONNECTIVITY

NETWORK LTE connectivity with integrated eSIM

WLAN Supports 802.11a/b/g/n/ac Wi-Fi standards

BLUETOOTH Supports Bluetooth 5, Bluetooth low energy

POSITIONING GPS/GLONASS

DIMENSIONS

WHEEL BASE 1340 mm

SEAT HEIGHT 800 mm

KERB WEIGHT 207 kg

GROUND CLEARANCE 160 mm